




Office of Nuclear Physics



# The MAJORANA DEMONSTRATOR: Concept, Design, Status

Vincente Guiseppe  
Univ. of South Carolina

Meeting on the Next Generation  $^{76}\text{Ge}$  Experiment  
Munich, Germany  
25 April 2016



OAK RIDGE NATIONAL LABORATORY



THE UNIVERSITY  
of NORTH CAROLINA  
at CHAPEL HILL



UNIVERSITY OF  
SOUTH CAROLINA



THE UNIVERSITY of  
TENNESSEE



# The MAJORANA DEMONSTRATOR



Funded by DOE Office of Nuclear Physics, NSF Particle Astrophysics, NSF Nuclear Physics with additional contributions from international collaborators.

**Goals:**

- Demonstrate backgrounds low enough to justify building a tonne scale experiment.
- Establish feasibility to construct & field modular arrays of Ge detectors.
- Searches for additional physics beyond the standard model.

Located underground at 4850' Sanford Underground Research Facility

Background Goal in the  $0\nu\beta\beta$  peak region of interest (4 keV at 2039 keV)

3 counts/ROI/t/y (after analysis cuts) Assay U.L. currently  $\leq 3.5$   
scales to 1 count/ROI/t/y for a tonne experiment

44-kg of Ge detectors


- 29 kg of 87% enriched  $^{76}\text{Ge}$  crystals
- 15 kg of  $^{\text{nat}}\text{Ge}$
- Detector Technology: P-type, point-contact.

2 independent cryostats

- ultra-clean, electroformed Cu
- 22 kg of detectors per cryostat
- naturally scalable

Compact Shield

- low-background passive Cu and Pb shield with active muon veto






# MAJORANA DEMONSTRATOR Implementation


## Three Steps

Prototype cryostat: 7.0 kg (10)  $^{nat}\text{Ge}$




## In shield Operation


June 2014-June 2015




May–Oct. 2015,  
Upgraded: Fall 2016  
Jan 2016 - present



May 2016



# MAJORANA Underground Laboratory




# Sensitivity vs. Exposure $^{76}\text{Ge}$



$^{76}\text{Ge}$  (87% enr.)

J. Detwiler



Inverted Ordering (IO)  
Minimum IO  $m_{\beta\beta}=18.3 \text{ meV}$ ,  
taken from using the  
PDG2013 central values of  
the oscillation parameters,  
and the most pessimistic NME  
for the corresponding isotope  
among QRPA, SM, IBM, PHFB,  
and EDF

Note : Region of  
Interest (ROI)  
can be single or  
multidimensional  
(E, spatial, ...)


Assumes 75% efficiency based on GERDA Phase I. Enrichment level is accounted for in the exposure

# 3 $\sigma$ Discovery vs. Exposure for $^{76}\text{Ge}$



$^{76}\text{Ge}$  (87% enr.)

J. Detwiler




Inverted Ordering (IO)

Minimum IO  $m_{\beta\beta}=18.3 \text{ meV}$ , taken from using the PDG2013 central values of the oscillation parameters, and the most pessimistic NME for the corresponding isotope among QRPA, SM, IBM, PHFB, and EDF

Note : Region of Interest (ROI) can be single or multidimensional (E, spatial, ...)

Assumes 75% efficiency based on GERDA Phase I. Enrichment level is accounted for in the exposure

# DEMONSTRATOR Background Model



# P-type Point Contact Detectors





Ultra-low background rate requires a pulse shape analysis (PSA) rejection of multi-site gamma events

## P-type Point-Contact (PPC) detectors

- No deep hole; small point-like central contact
- Length is shorter than standard coaxial detector
- Simple, cost-effective, low background
- Localized weighting potential gives excellent multi-site rejection
- Low capacitance ( $\sim 1$  pF) gives superb resolution at low energies

Rising edge “stretched” in time  
⇒ improved PSA



Hole  $v_{drift}$  [mm/ns]  
with paths and  
isochrones

# MAJORANA Detector Choice



## MAJORANA DEMONSTRATOR


### Natural Detectors

- CANBERRA modified BEGe
- $\sim 70 \text{ mm} \times 30 \text{ mm}$
- $\sim 650 \text{ g}$  each
- Made in Meriden, CT, USA; different from the Olen-type used in GERDA



### Enriched Detectors

- ORTEC PPC
- $\sim 70 \text{ mm} \times 50 \text{ mm}$
- $\sim 900 \text{ g}$  each
- All production (zone refinement, crystal pull and diode production) in Oak Ridge, TN, USA
- Production began in Nov. 2012



# Delivered enr<sup>76</sup>Ge Detectors




Vendor: AMETEK/ORTEC

Enriched detector production completed in June 2015

Total enriched detector mass = **29.683 kg / 35 detectors**

Mean FWHM at 1333 keV = **1.88 keV**




MJDF-2016-04-18-002-R1

# Material Purity



## The detector

- Ge metal zone refined and pulled into a crystal that provides purification
- Limit above-ground exposure to prevent cosmic activation
- Deep underground operation




## Detector mounts

- Ultra-pure plastic and electro-formed Cu
- Low mass design
- Custom cable connectors and front-end boards
- Carefully selected plastics (PTFE, PEEK, Vespel)
- Fine Cu coaxial cables



## Cryostat and inner shielding

- Underground electro-formed Cu



# MAJORANA Electroformed Cu



MAJORANA operated 10 baths at the Temporary Clean Room (TCR) facility at the 4850' level and 6 baths at a shallow UG site at PNNL. All copper was machined at the Davis campus.

The electroforming of copper for the DEMONSTRATOR successfully completed in May of 2015 but we continued to operate baths in the TCR for additional material until March 2016.

- 2654 kg of electroformed copper produced.
- 1196 kg was installed in the Demonstrator.

Electroforming Baths in TCR



Inspection of EF copper on mandrels




Th decay chain (ave)  $\leq 0.1 \mu\text{Bq}/\text{kg}$   
U decay chain (ave)  $\leq 0.1 \mu\text{Bq}/\text{kg}$

EF copper after turning on lathe





# Cu Production and Machining



Underground Cu electro-forming laboratory produces all of the ultra-pure inner Cu





# Cu Production and Machining



All parts are uniquely tracked through machining, cleaning, and assembly by a custom-built database.

Cu machining in an underground clean room machine shop complete April 2016



# Cu Part Cleaning



Cleaning of Cu parts by acid etching and passivation

# Assembled Detector Unit and String





Electroformed  
Copper

PTFE

PFA + fine Cu  
coaxial cable

Front-End Elec.




String Assembly



# Detector Readout Components




Shipping  
Restraint



Fine Cu coaxial cable and  
clean connectors





Custom low mass front-end boards  
Clean Au+Ti traces on fused silica  
Amorphous Ge resistor  
FET mounted with silver epoxy  
EFCu + low-BG Sn contact pin




Connectors reside on top of cold  
plate.  
In-house machined from Vespel.  
Axon' pico co-ax cable.  
Low background solder and flux.

# Glovebox Assembly




# Detector Units



V. E. Guiseppi

Meeting on the Next Generation  $^{76}\text{Ge}$  Experiment - April 2016





- All detector related assembly performed in  $\text{N}_2$  purged gloveboxes.
- All detectors' dimensions recorded by optical reader.

# Detector Units and Strings



Detector units and strings built inside a glovebox with a radon-reduced, dry N<sub>2</sub> environment



# Detector Module



- A self contained vacuum and cryogenic vessel
- Contains a portion of the shielding
- Can be transported for assembly and deployment



Cryostat mated to the glovebox for string installation

# Detector Module



First string of  $^{76}\text{Ge}$  in Cryostat 1


Cabling on top of cold plate




# Detector Module



Loading of  $^{enr}\text{Ge}$  in Cryostat 1



Loading of  $^{enr}\text{Ge}$  in Cryostat 2





# Passive Shielding and Muon Veto



Pb and outer Cu shield installed



Module deployment



# Passive Shielding and Muon Veto





Module deployment



Muon panels

# The Inner Copper Shield




- Extensive time to electro-form the Cu parts.
- String parts higher priority for machining.
- Hence installed after shield constructed.
- Expect x10 reduction in background from other shield materials.



# The MAJORANA Calibration system




- Line sources are deployed from outside the shielding within a tube that surrounds each cryostat.
- $^{228}\text{Th}$  (11.6 kBq) and  $^{60}\text{Co}$  (6.3 kBq) sources available.
- Calibration tube is externally purged during calibration.
- Several sensors monitor the position of the source and the status of the system.




# $^{228}\text{Th}$ Calibration Spectrum in Module 1 (DS0)



One enriched detector spectrum within a string mounted in Module 1 and inside shield. FWHM 3.6 keV at 2.6 MeV



# Ge Detector PSD Performance in Module 1 (DS1)



$^{208}\text{TI DEP}$  (single site events) fixed to 90%

$^{208}\text{TI SEP}$  (multi-site events) reduced to 10%

# Data Set Parameters



Data Set	Prototype Module	Module 1 no inner shield	Module 1 with inner shield
mnemonic	DS-PM	DS0	DS1
Operation Dates	9/18/14 – 4/17/15	6/26/15 – 10/7/15	12/31/15 – 4/14/16*
Run Time	211 d	103.15 d	104.68 d
Live Time	138.22 d	47.73 d	54.70 d
Fraction Live	0.65	0.46	0.52
Enriched Ge Exposure	0 kg d	$510.2 \pm 1.1$ kg d	$650.41 \pm 0.30$ kg d
Natural Ge Exposure	701.7 kg d	$186.6 \pm 0.6$ kg d	$91.35 \pm 0.15$ kg d

\*Data taking ongoing

Dry-run of analysis and data production  
 Found known backgrounds and addressed  
 2 observed backgrounds

# Module 1 Data Set Duty Cycles





Break for Module 1 planned improvements

---

DS0 (days) No inner shield	DS1 (days) with inner shield
June 26, – Oct. 7, 2015	Dec. 31, 2015 – Apr. 14, 2016*

---

Total	103.15	104.68
Total acquired	88.04	97.49
Physics	47.73	54.70
High radon	11.76	7.32
Disruptive Commissioning tests	13.10	28.61
Calibration	15.44	6.86
Down time	15.11	7.19



\*Data taking ongoing

# Module 1 Improvements – Fall 2015



Operated in-shield June 2015 - Oct. 2015

- Partial shielding and some high-background components

During Oct.- Dec. 2015 performed planned improvements to Module 1.

- Installed inner Cu shield: Decrease background contribution from outer Cu shield and Pb by factor of about 10.
- Replaced Kalrez O-rings in cryostat: These o-rings contributed to our background. Replaced with PTFE.

Kalrez: Th ~ 2000-4000 ppt. Expect about 80 c/ROI t y.

PTFE sheet: significant reduction in BG compared to Kalrez.

Crossarm Shielding: Added to decrease background contributions from electronics-breakout box region.

Repaired non-operating detectors and upgrade cables:


- Repairing non-operating detectors (cable connection, HV connection, LMFE replacement, ...)

# Delayed Charge Recovery and Alphas




- Alpha background response observed in Module 1 commissioning (DS0)
  - Identified as arising from alpha particles impinging on passivated surface
- Results in prompt collection of some energy, plus very slow collection of remainder
- Enables a powerful PSA rejection of alpha events
- “Delayed Charge Recovery” parameter related to slope of tail

Example pole-zero  
corrected waveforms



Slow drift of charges along  
passivated surface results in  
very slow signal component




# Rn Simulation Compared to Data











Rn purge-off test Sept. 2015, during Module 1 commissioning (DS0).

Rn simulation compared to data. Fit around 609-keV peak.

Fit is 8.5 pCi/L, near room value of  $6.91 \pm 0.06$  pCi/L. No shield-level value.



# Module 1 String Layout



P#####L ORTEC PPC, enriched, detector mass 16.8 kg

B#### Canberra BEGe, natural, detector mass 5.7 kg

29 total detectors

# Module 1 Detector Status




	6/26/15 – 10/7/15	12/31/15 – Present
mnemonic	DS0	DS1
Total Number of Detectors Installed	29	29
Enriched Detectors	20	20
Num. used in Analysis	14	15
Natural Detectors	9	9
Num. used in Analysis	7	3
Active Natural Mass	3.9 kg of 5.7 kg	1.7 kg of 5.7 kg
Active Enriched Mass	10.7 kg of 16.8 kg	11.9 kg of 16.8 kg

Unbiased Detectors - Lost connections, leakage current, noisy response, HV instability  
May re-work Module 1 as Module 2 commissioning progresses

# The MAJORANA Blindness Plan



Minimum exposure to reach  $2.1 \times 10^{25}$  yr half-life limit as a function of background.



- Data pre-scaling scheme, 25% open. 31 h open followed by 93 h blind.
- If background is near goal, require 15-20 kg yr of exposure to reach present half-life limit in Ge. Hence plan to remove blindness after 15 kg yr.
- Specialized physics analyses (dark matter, e.g.) will have different blind exposure requirements based on physics goals. A certain region of the spectrum may have blindness removed at a lower exposure, for example.

# MJD Summary



- Assembly and construction concluding at Sanford Davis Campus laboratory.
- Based on assays, material backgrounds projected to meet cleanliness goals.
- Successful reduction and refinement of  $^{76}\text{Ge}$  with 98% yield.
- Electroformed copper completed at SURF and PNNL.
- AMTEK (ORTEC) produced 35 detectors, 29.7 kg, from the  $^{76}\text{Ge}$ .
- All detectors underground at SURF.
- Shield nearly complete. Some poly layers are not yet installed
- Module 1, in-shield running from June – Sept. 2015. Final installations complete and re-installed in shield Dec. 2015. Module 1 operating in shield
- Module 2 construction and assembly proceeding. Scheduled to start commissioning in May 2016.
- Predict  $T_{1/2} = 1.2 \times 10^{26}$  y (90% Sensitivity) and  $T_{1/2} = 1.2 \times 10^{26}$  y (3 $\sigma$  Discovery)
  - MJD 100 kg-year at 3.5 counts/ROI-t-y





# The MAJORANA Collaboration



[Black Hills State University, Spearfish, SD](#)

Kara Keeter

[Duke University, Durham, North Carolina , and TUNL](#)

Matthew Busch

[Joint Institute for Nuclear Research, Dubna, Russia](#)

Viktor Brudanin, M. Shirchenko, Sergey Vasilyev, E. Yakushev, I. Zhitnikov

[Lawrence Berkeley National Laboratory, Berkeley, California and the University of California - Berkeley](#)

Nicolas Abgrall, Adam Bradley, Yuen-Dat Chan, Susanne Mertens, Alan Poon, Kai Vetter

[Los Alamos National Laboratory, Los Alamos, New Mexico](#)

Pinghan Chu, Steven Elliott, Johnny Goett, Ralph Massarczyk, Keith Rielage, Larry Rodriguez, Harry Salazar, Brandon White, Brian Zhu

[National Research Center 'Kurchatov Institute' Institute of Theoretical and Experimental Physics, Moscow, Russia](#)

Alexander Barabash, Sergey Konovalov, Vladimir Yumatov

[North Carolina State University](#)

Alexander Fulmer, Matthew P. Green

[Oak Ridge National Laboratory](#)

Fred Bertrand, Kathy Carney, Alfredo Galindo-Uribarri, Monty Middlebrook, David Radford, [Elisa Romero-Romero](#), Robert Varner, Chang-Hong Yu

[Osaka University, Osaka, Japan](#)

Hiroyasu Ejiri

[Pacific Northwest National Laboratory, Richland, Washington](#)

Isaac Arnquist, Eric Hoppe, Richard T. Kouzes

[Princeton University, Princeton, New Jersey](#)

Graham K. Giovanetti

[Queen's University, Kingston, Canada](#)

Ryan Martin

[South Dakota School of Mines and Technology, Rapid City, South Dakota](#)

Colter Dunagan, Cabot-Ann Christofferson, Stanley Howard, Anne-Marie Suriano, Jared Thompson

[Tennessee Tech University, Cookeville, Tennessee](#)

Mary Kidd

[University of North Carolina, Chapel Hill, North Carolina and TUNL](#)

Thomas Caldwell, [Thomas Gilliss](#), Reyco Henning, Mark Howe, [Samuel J. Meijer](#), [Benjamin Shanks](#), Christopher O'Shaughnessy, [Jamin Rager](#), [James Trimble](#), [Kris Vorren](#), John F. Wilkerson, Wenqin Xu

[University of South Carolina, Columbia, South Carolina](#)

Frank Avignone, Vince Guiseppe, David Tedeschi, [Clint Wiseman](#)

[University of Tennessee, Knoxville, Tennessee](#)

Yuri Efremenko, [Andrew Lopez](#)

[University of Washington, Seattle, Washington](#)

Tom Burritt, [Micah Buuck](#), Clara Cuesta, Jason Detwiler, [Julieta Gruszko](#), [Ian Guinn](#), David Peterson, R. G. Hamish Robertson, Tim Van Wechel

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Physics, the Particle Astrophysics and Nuclear Physics Programs of the National Science Foundation, and the Sanford Underground Research Facility.



# The MAJORANA Collaboration





This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Nuclear Physics, the Particle Astrophysics and Nuclear Physics Programs of the National Science Foundation, and the Sanford Underground Research Facility.

# Backup Slides

---



# HV Connection Updates



Plan to add clamp nut and spring washer.



---

email to send Group Résumés slides

[guiseppe@sc.edu](mailto:guiseppe@sc.edu)